ROTOPRINT - 750 MX

On Line Printing, Gusseting **Cutting & Rewinding Machine**



Compact, Powerful, Efficient

TECHINICAL FEATURES

- no overhead crane required.
- 2. Brake drum tension control provided on unwinder with hydro web guiding system.
- 3. Pneumatic system maintain proper tension of fabric thus ensuring o-o print registration at high printing speed of 70 -80 meters per minute.
- 4. Maximum cutting length 1300 mm
- 5. Maximum printing width 750mm
- 6. A special gearbox system is incorporated which is multi-functional.
- changeover of rotation for printing 3:1,

- clockwise and 360° anti-clockwise to adjust printing without switching off the and has universal locking.
- i.e : Lateral side shifting also provided and can be operated without switching Off the machine
- minimized thus the machine is operation. absolutely noise-free
- 7. Each printing station is of extremely robust design with central single locking to ensure that the printing is very - very sharp since there is no vibration by this design.
- are of bigger diameters so there is no variation in fabric width. splashing of ink even at high speeds.

- 1. Turret unwinder to load two fabric rolls i.e: Printing drum can be rotated 360° 9. The adjustment of ink pressure and rollerpressure is with micro metric screws
 - 10. A fire proof hot air blowers drying system ensures a very safe and effective drying of printing even at high speed of 80 mt / min.
 - i.e : Total number of external gears 11. Full digital control panel for easy
 - 12. An Rotary cutting unit with collection
 - 13. An four roll surface rewinder ensures continuous rewinding.
- 14. A special gusseting system ensures i.e: Dual rotation by lever ensures 8. All Anilox rollers and rubber rollers smooth gusset operation even if there is a